



Primer

FRA/A - FRA/AS - FRA/AVS VACUUM IRONING TABLES WITH BOILER

FEATURES

Models equipped with built-in vacuum unit and electric boiler :

- Utility ironing table with suction and electrically heated board, temperature controlled by a thermostat.
- Built-in electric steam boiler.
- With standard board (1.200 x 400 x 250).
- Automatic water feeding.
- Steam iron
- Drain and feed pump
- Automatic pressure control
- Foot pedal control
- Adjustable height of board for models FRA/A PLUS and FRA/AS from 750 to 950 mm

FRA/A : heated and vacuum table

FRA/AS : heated, vacuum and blowing table

- Built-in single-phase suction and blowing device, controlled by double pedal
- Requires an external compressed air supply (consumption 5 l/min)

FRA/AVS : heated, vacuum, up-steaming and blowing table

- Built-in single-phase suction and blowing device, controlled by double pedal
- Requires an external compressed air supply (consumption 5 l/min)



OPTIONS

- Swinging arm with suction and heated sleeve shape.
- Steam gun
- Sliding trolley for iron with balancer and lighting
- Second steam iron

TECHNICAL DATA	UNIT.	FRA/A PLUS	FRA/A	FRA/AS	FRA/AVS
CAPACITY					
Boiler	-	Yes	Yes	Yes	Yes
Boiler capacity	l	5	5	5	7
Board dimensions	mm	1.200 x 400 x 270	1.200 x 400 x 250	1.200 x 400 x 270	1.200 x 400 x 250
Adjustable height of board		Yes	No	Yes	No
OPTIONS					
Swinging arm with heated sleeve shape	-	Opt	Opt	Opt	Opt
Steam gun	-	Opt	Opt	Opt	Opt
Sliding trolley with balancer and lighting	-	Opt	Opt	Opt	Opt
Second steam iron assembly	-	Opt	Opt	Opt	Opt
POWER					
Vacuum Motor	kW	0,45	0,45	0,45	0,45
Pump Motor	kW	-	-	-	0,75
Iron Heater	kW	0,83	0,83	0,83	0,83
Board heater	kW	1	1	1	-
Boiler Heater	kW	3,9	3,9	3,9	6-7,5
Sleeve-arm heater (option)	kW	0,09	0,09	0,09	0,09
CONNECTIONS					
Ø Water inlet	BSP	3/8"	3/8"	3/8"	3/8"
Ø Boiler exhaust (with boiler)	BSP	3/8"	3/8"	3/8"	3/8"
Ø Steam inlet	BSP	-	-	-	-
Steam pressure	BAR	2,8	2,8	2,8	4,5
Steam Consumption	Kg/h	-	-	-	-
Ø Air inlet	BSP	-	-	-	1/4"
Air pressure	BAR	-	-	-	4-8
Air Consumption	NI/min	-	-	-	5
DIMENSIONS / DIMENSIONS WITH PACKING					
Net width / Gross width	mm	1.500 / 1.520	1.550 / 1.520	1.500 / 1.520	1.680 / 1.880
Net depth / Gross depth	mm	600 / 580	580 / 580	600 / 580	580 / 680
Net height / Gross height	mm	1.800 / 1.120	950 / 1.140	1.800 / 1.120	920 / 1.270
Net weight / Gross weight	kg	100 / 116	87 / 103	100 / 116	141 / 165
Volume	m ³	1,62 / 0,99	0,85 / 1,01	1,62 / 0,99	0,90 / 1,62
OTHERS					
Voltage 50-60 Hz	Hz	230/400V III	230/400V III	230/400V III	230/400V III
Sound level	dB	70	68	70	75

