



Primer

MAN-AM-V FORM FINISHER FOR COATS AND SIMILAR

FEATURES

- **Automatic tensioning finisher for classic coats, overcoats and similar garments**
- **Without boiler:** to be connected to central steam supply
- Working cycle by electronic card with 9 stored finishing programs, very easy to modify
- Telescopic shape till 1.500 mm
- Special 350° revolving "body" form plus automatic "front & rear" paddle clamps
- Sensor for the "automatic research of the height" of the garment
- Double "antistretching" system in large (waist) and in height (length)
- Mechanical adjustable shoulder group and dedicated "collar" clamp
- Damper for air-volume regulation
- For central compressed air supply line
- Air working pressure 5-6 bar.
- Air consumption 8/9 NI/min.
- Can be installed with steam generator GE-24 - 22 kw
- Voltage : 400V III+N / 230V III 50-60 Hz



OPTIONS

- Steam iron assembly

TECHNICAL DATA	UNIT.	MAN-AM-V
GENERAL DETAILS		
Board dimensions	mm	-
Boiler	-	No
Boiler capacity	l	-
Compressor	-	-
Group of Iron	-	Opt
Steam gun	-	-
Polished upper buck	-	-
POWER		
Vacuum Motor	HP	-
Pump Motor	HP	-
Compressor motor (Mod. with option)	-	-
Boiler Heater (Mod. with option)	-	-
Fan motor	HP	2
CONNECTIONS		
Ø Water inlet	BSP	-
Ø Boiler exhaust (mod. with boiler)	BSP	-
Ø Steam inlet	BSP	1/2"
Ø Condensate outlet	BSP	1/2"
Steam pressure	BAR	4-8
Steam Consumption	Kg/h	10-15
Ø Air inlet	BSP	1/4"
Ø Air outlet	mm	1/4"
Air pressure	BAR	5-6
Air Consumption	NI/min	8/9
DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	mm	650 / 800
Net depth / Gross depth	mm	900 / 1.050
Net height / Gross height	mm	1.600-2.100 / 1.850
Net weight / Gross weight	kg	160 / 230
Volume	m ³	1,22 / 1,55
OTHERS		
Voltage	Hz	230/400V III 50/60
Sound level	dB	70

