



Primer

MAN-PA-A / MAN-PA-V UTILITY FORM FINISHER

FEATURES

- Fully automatic cycle by electronic card.
- Steaming and drying time controlled by 3 timers.
- 9 different cycles available
- Adjustable shoulder and sleeve widths
- Rotation of dummy support at 360°
- Does not require compressed air

MAN-PA-V (WITHOUT BOILER)

- Without steam boiler, to be connected to a central steam supply
- It needs a steam inlet and outlet
- Can be installed with steam generator GE-24 - 12 kw
- Voltage 400 V III +N / 230 V III 50-60 Hz

MAN-PA-A (SELF-CONTAINED)

- Complete with built-in steam boiler 18 lt
- Automatic water feeding
- Automatic pressure control (4,5 bar)
- Voltage 400 V III +N / 230 V III 50-60 Hz.



TECHNICAL DATA	UNIT.	MAN-PA-A	MAN-PA-V
GENERAL DETAILS			
Board dimensions	mm	-	-
Boiler	-	Yes	No
Boiler capacity	l	18	-
Compressor	-	-	-
Group of Iron	-	-	-
Steam gun	-	Opt	-
Polished upper buck	-	-	-
POWER			
Vacuum Motor	HP	-	-
Pump Motor	HP	0,8	-
Boiler Heater (Mod. with option)	kW	12	-
Fan motor	kW	1	1
CONNECTIONS			
Ø Water inlet	BSP	3/8"	-
Ø Boiler exhaust (mod. with boiler)	BSP	1/2"	-
Ø Steam inlet	BSP	-	3/8"
Ø Condensate outlet	BSP	-	3/8"
Steam pressure	BAR	4,5	4,5
Steam Consumption	Kg/h	10-15	10-15
Ø Air inlet	BSP	-	-
Ø Air outlet	mm	-	-
Ø Air pressure	BAR	-	-
Ø Air Consumption	NI/min	-	-
DIMENSIONS / PACKING DIMENSIONS			
Net width / Gross width	mm	1.360 / 1.390	1.200 / 1.390
Net depth / Gross depth	mm	610 / 640	580 / 640
Net height / Gross height	mm	1.780 / 1.910	1.620 / 1.910
Net weight / Gross weight	kg	130 / 151	88 / 109
Volume	m ³	1,48 / 1,70	1,13 / 1,70
OTHERS			
Voltage	Hz	230/400V III 50-60	230/400V III 50-60
Sound level	dB	70	70

01. Electrical connection
02. Condensate
03. Steam inlet

